

# DT2063N

## Detector analógico térmico con salida de piloto remoto. Serie 2000.

### General

---

The DT2063N is a 2000 series protocol, addressable heat detector certified to class A2R. It provides good looks as well as top features, including a rate-of-rise algorithm that allows the device to raise the alarm before the fixed temperature trigger point is reached. Dual fire LEDs indicate an alarm visible from all directions, eliminating the need for special detector orientation on installation, whilst a remote indicator output is provided as standard on every device.

### Installation Friendly

---

The DT2063N is individually identified by setting an address through two rotary switches. The address is a straight numerical value and does not require binary or hexadecimal conversions, significantly reducing the risk of incorrect addressing.

All 2000 series detectors are compatible with a standard base that makes them easily interchangeable.

### State of the Art Communication

---

Panel to device communication is provided through a powerful SIA protocol featuring multiple bus cycle codes and CRC error checking and ensuring reliable communications between the device and the control panel.

This enhanced protocol ensures the overall integrity and error free operation of the full system, without compromising speed.

### Extended Applications

---

For varied applications the fixed temperature trigger level of the DT2063N may be set from the CIE to accommodate higher activation temperatures.

A comprehensive line of complimentary devices completes the 2000 series portfolio:

- common use detector bases
- optical, temperature and multi-sensors
- standalone and base isolators
- sounder circuit controllers
- conventional zone monitoring units
- various supervised and non-supervised I/O units
- a comprehensive line of manual call points
- loop powered notification devices and beam detectors



### Details

---

- Dual thermistors
- Remote signaling capabilities
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range including optical and multi sensors
- Full range of I/O units and accessories
- Optional isolator base
- EN54:5 approved and CPR certified

# DT2063N

Detector analógico térmico con salida de piloto remoto. Serie 2000.

## Technical specifications

### General

Indicación de estado	Dual LED
Compatibilidad	Aritech 2000 systems
Niveles de alarma	5
Conectividad	2-wire loop & remote indicator

### Eléctrico

Voltaje de funcionamiento	17 to 28 VDC
Consumo de corriente	< 270 $\mu$ A (quiescent at 24 VDC) 4.7 mA (alarm at 24 VDC)

### Detección

Principio de detección	Heat
Área de cobertura	< 80 m <sup>2</sup>
Temperatura de alarma	> +40°C
Rate-of-rise	Class A2

### Salida

Cantidad de salidas	1
Programable	No
Salida de alarma remota	4.7 mA

### Físico

Dimensiones físicas	100 x 50 mm ( $\varnothing$ x H)
Peso neto	83 g
Color	Blanco nuboso (RAL 9001)
Tipo de Montaje	Montaje en el techo
Material	Plástico

### Medioambiental

Antivandálico	No
Temperatura de funcionamiento	-10 to +60°C
Temperatura de almacenamiento	-10 to +70°C
Humedad relativa	10 to 95% non-condensing
Entorno	Interior
Clasificación IP	IP20
Temperatura ambiente	+25°C

### Estándares y regulaciones

Cumplimiento	CE, REACH, RoHS 2, WEEE
Certificación	CPR
Normativas	EN54-5

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 29 November 2019 - 10:31



**United  
Technologies**

Climate | Controls | Security