

FAW355

Piloto convencional estroboscópico a 24Vcc para pared. Rojo con lente roja. IP65. Base alta para tubo vista.

General

The FAW355 is a general purpose wall mount LED beacon for fire alarm applications. It features a special base deep containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of W-2.4-7.5, each FAW355 may be mounted up to 2.4m high and cover a square room of 7.5 x 7.5m with a single device.


Easy and Fast Installation

The FAX350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these beacons use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The FAX350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.



Details

- Automatic synchronisation
- Anti-Tamper locking mechanism
- Deep mouting base
- Wiring directly to base
- Flash rate selectable
- IP65 Ingress protection

FAW355

Piloto convencional estroboscópico a 24Vcc para pared. Rojo con lente rojo. IP65. Base alta para tubo vista.

Technical specifications

Eléctrico

Voltaje de funcionamiento	17 to 60 VDC
---------------------------	--------------

Físico

Dimensiones físicas	100 x 104 mm (Ø x D)
Peso neto	250 g
Color	Rojo
Posición de montaje	Pared
Altura de montaje	up to 2.4 m
Material	Policarbonato de alto impacto

Medioambiental

Temperatura de funcionamiento	-25 to +70°C
Humedad relativa	5 to 95% noncondensing
Entorno	Interior, Exterior
Clasificación IP	IP65

Estándares y regulaciones

Certificación	EN54-23
---------------	---------

Operation

Continuous

Current consumption

20mA @ 0.5 Hz / 40mA @ 1 Hz

Flash rate

0.5Hz or 1Hz

Automatic synchronisation

Phased start

Line monitoring input

Polarised input


Flash colour

Red

EN54-23 rating

Light coverage	W-2.4-7.5
Floor coverage	up to 7.5 x 7.5 m

EN54-23 Coverage: W-2.4-7.5



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 13 August 2020 - 16:52

