

Product data sheet

Specifications



Sounder VAD, WSS-PC-N33, without isolator, wall mounted, EN54-23

FFS06711746

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Audible visual alarm device

Complementary

Colour tint	Base: pure white Lens: clear
[Ue] rated operational voltage	15...29 V DC
Current consumption	120 µA standby 14.5 mA at 15 V DC alarm
Signalling type	32 tones alarm
Acoustic level	94...100 dBA at at 1m
Type of setting	Volume: low settings Volume: medium settings Volume: high settings
Local signalling	LED red flashing at 1 Hz: alarm
Coverage class	Open
Cable cross section	1.5...2.5 mm²
Device mounting	Base mounting low profile Base mounting deep base Base mounting waterproof base
Diameter	121 mm
Height	64 mm (low profile) 119 mm (deep base) 119 mm (waterproof base)
Net weight	238 g

Environment

Standards	EN 54-23 EN 54-3
Product certifications	CPR LPCB
IP degree of protection	IP21C with low profile base IP44 with deep base IP65 with waterproof base
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	270 g
Package 1 Height	5 cm
Package 1 width	10 cm
Package 1 Length	12 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information