

# DP721RT

## Detector convencional óptico-térmico con salida de relé. Serie 700.

### Preventing false alarms with self diagnostics

---

All Aritech 700 series smoke detectors continuously monitor their sensitivity and operational status. Background drift is daily compensated to maintain the original calibrated sensitivity within the required limits.

Once a day the detector performs a full diagnostic test that includes dynamically testing the sensing chamber and internal electronics. If a detector drifts out of sensitivity range or fails the internal diagnostics test, this is reported back to the panel and indicated on the detector with a yellow fault LED.

### Maintenance friendly sensitivity level test mode

---

The 700 Series photoelectric detectors include a sensitivity test mode that may be activated by simply holding a magnet near the detector's test point. This initiates a self-diagnostic routine and provides visual indication if service is required. This test mode allows field sensitivity testing without the requirement for external meters or test gas.

### Field cleaning and service

---

The photoelectric sensing chamber unclips from the detector for easy field cleaning and service. During regular maintenance the detector cover can be removed, the optical chamber removed and replaced by a low cost, new chamber. On power up the detector auto-calibrates and returns to normal operating mode without any further intervention.

### The right detector for the right job

---

For a truly fast and broad-spectrum detection the DP721RTA offers both optical and heat sensors. The interaction of both the smoke and heat algorithms ensure a quick response to both flaming and smouldering fires.

All bases are provided with an integral locking tab for extra security if required. Bases are equipped with a shorting bar between IN and OUT that opens when the head is installed and that may be manually restored when removing the head. This simplifies cable continuity testing.

### Note:

---

The DP721RTA must not be used in applications requiring compliance with commercial or residential fire standards such as EN54-5/EN54-7/EN54-29/CEA4021/EN14604. Always ensure compliance with local codes and standards.



### Details

---

- Automatic self diagnostics with dynamic full detector and sensitivity test
- High false alarm immunity with floating background with drift compensation
- Separate fire and fault LEDs for unambiguous alarm reporting
- Wide operating voltage for use on most conventional systems
- Polarity insensitive for carefree installation
- COM/NO/NC contacts for easy supervision on any system
- Manual self diagnostic with visual sensitivity indication
- Field exchangeable and disposable optical chamber

# DP721RT

## Detector convencional óptico-térmico con salida de relé. Serie 700.

### Technical specifications

#### General

Indicación de estado	White LED (red in alarm), Yellow LED (test & fault)
User interface	LEDs
Compatibilidad	Aritech conventional zones
Tensión de rearme	<2.5 V max
Tiempo de rearme	1 s
Niveles de alarma	1
Conectividad	Aritech conventional base

#### Eléctrico

Tipo de fuente de alimentación	Zone powered
Voltaje de funcionamiento	8.5 to 33 VDC
Consumo de corriente	100 $\mu$ A (quiescent at 24 VDC) <60 mA (in alarm at 24 VDC)

#### Detección

Principio de detección	Optical light scatter and heat
Monitoring	Alarm threshold, Contamination level
Sensibilidad	10%/m (+1.6%, -3.3%)
Longitud de la zona	Cable dependent
Temperatura de alarma	> +40°C
Rate-of-rise	8°C/min above 40°C, Class A2

#### Salida

Cantidad de salidas	1
Ratio y tipo de salida	Relay (2 A at 30 VDC, 1 A at 120 VAC)
Programable	No
Salida de alarma remota	NA

#### Físico

Dimensiones físicas	100 x 50 mm ( $\varnothing$ x H)
Peso neto	115 g
Color	Blanco nuboso (RAL 9001)
Tipo de Montaje	Montaje en el techo
Material	Plástico

#### Medioambiental

Antivandálico	No
Temperatura de funcionamiento	-10 to +60°C
Temperatura de almacenamiento	-10 to 70°C
Temperatura ambiente	+25°C
Humedad relativa	0 to 95% non-condensing
Entorno	Interior
Clasificación IP	IP43

#### Estándares y regulaciones

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CPR
Normativas	EN54-7



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.