



Triple IR flame detector, base mounted

FFS06725285

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Flame detector
Sensor type	Infrared sensor

Complementary

[Ue] rated operational voltage	17...28 V DC
Current consumption	2.5 mA standby 4.2 mA alarm 9 mA power-up surge 5 mA remote LED
Material	Body PC (polycarbonate) Terminal nickel plated stainless steel
Output type	Remote LED optional
Mounting location	Indoor use only
Field of view	90° cone
Colour	white
Diameter	100 mm
Height	40 mm 48 mm with mounting base)
Product weight	150 g 210 g with mounting base

Environment

Standards	Class 1 EN 54-10 Class 3 EN 54-10
Product certifications	LPCB CPR
IP degree of protection	IP66
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-40...70 °C

Suurim lubatud võrreldavate toodete arv on täis. Avage jaotis Võrreige tooteid #LINK# ja kustutage jätkamiseks mõni toode

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	250 g
Pakk 1 kõrgus	5 cm
Pakk 1 laius	12,5 cm
Pakk 1 pikkus	12,5 cm

Offer Sustainability

ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.