

# AS2364W

## 2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

### General

---

The AS2364W is a WHITE bodied, deep base addressable room sounder for fire alarm systems running 2000 series addressable fire protocol. Multiple tone selection and full CPD approval ensure conformance to local regulations.

The sounders operate over a 2-wire 2000 series loop and are loop powered i.e. no external power supply is required. They are compatible with automatic phased-start synchronisation controlled from the fire panel. The AS2364W has a IP65 enclosure.

### Installation

---

Device cabling is done to the base and allows the sounder to be fitted and locked into position afterwards. A separate earth terminal is provided in the base for connecting the screen or functional earth when required.

### Efficient and versatile

---

These sounders can be put into different operating modes depending on local requirements. It provides high sound output at a low current, thus reducing power standby requirements and overall system cost. They are supplied with high/low volume settings as standard, allowing final audio adjustments to be made during installation.

The sounder is tone selectable during installation. 32 tone settings are available.



### Details

---

- Loop powered
- High sound output with low current consumption
- Multiple tone selection
- Suitable for multiple stage evacuation with up to 3 pre-set tones
- Automatic synchronisation
- IP65 rated
- CPD certified

# AS2364W

## 2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

### Technical specifications

---

#### Electrical

---

Operating voltage	17 to 28 VDC
-------------------	--------------

---

#### Sounder

---

Frequency	400 - 2850 Hz *
Output @ 90° ± 3 dB(A)	97dBA dBA at 1m *
Selectable tones	32
Frequency range	400 - 2850 Hz *
Volume adjustment	8 dB

---

#### Physical

---

Physical dimensions	100 x 104 mm (Ø x H)
Net weight	250 g
Body	High Impact Polycarbonate
Weight	250 g
Dimensions (dia x h)	100 x 104 mm
Cable size	0.28 mm <sup>2</sup> to 2.5 mm <sup>2</sup>

---

#### Environmental

---

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor
IP rating	IP65
Operating Temperature	-10°C to +55°C
Storage temperature	-10°C to +55°C
Relative humidity (non condensing)	5% to 95%
IP Rating	IP65

---

#### Standards & regulation

---

Certification	EN54-3
---------------	--------

---

#### Operating voltage

---

17-28 VDC
-----------

---

#### Supply current @ 24 VDC

---

Switch on surge	< 1.2 mA
Quiescent	310 µA
Activated (Sounder)	5.1 mA
Activated (Beacon)	NA

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 24 January 2022 - 10:32