

Product data sheet

Specifications



Dual input-single output module, EM-221E

FFS06717021

! Discontinued on: 28 April 2022

! To be discontinued

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Input/output module

Complementary

[Ue] rated operational voltage	15...30 V DC
Current consumption	340 μ A at 24 V DC standby 660 μ A at 24 V DC standby LED on
Load current	2 A at 30 V DC resistive load load for relay output
Cable cross section	0...2.5 mm ²
Number of inputs	2 for input circuit
Number of outputs	1 relay output
Length	93 mm
Height	23 mm
Width	94 mm
Net weight	100 g

Environment

Product certifications	LPCB
IP degree of protection	IP30
Relative humidity	5...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	110.0 g
Package 1 Height	11 cm
Package 1 width	5 cm
Package 1 Length	11 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
