

Product data sheet

Specifications



Mains switching output module, EM-201E-240

FFS06717041

⚠ To be discontinued on: 25 April 2023

⚠ To be discontinued

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Output module

Complementary

[Ue] rated operational voltage	15...30 V DC
Current consumption	275 µA at 24 V DC standby maximum 445 µA at 24 V DC alarm LED on
Load current	5 A at 30 V DC resistive load load for relay output 5 A at 250 V AC resistive load load for relay output
Cable cross section	0...1.5 mm²
Length	134 mm
Height	40 mm
Width	139 mm
Net weight	195 g

Environment

Product certifications	LPCB
IP degree of protection	IP50
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	210.0 g
Package 1 Height	14 cm
Package 1 width	4 cm
Package 1 Length	14 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information