

FE240

Retenedor electromagnético de 400N para montaje empotrado.

General

The FE240 is a flush mount door holder, with a Bayblend housing, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE240 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE240

Retenedor electromagnético de 400N para montaje empotrado.

Technical specifications

General

| | |
|--------------------------|-----|
| Holding force N (Newton) | 400 |
|--------------------------|-----|

| | |
|---------------------|----|
| Botón de liberación | No |
|---------------------|----|

| | |
|------------------------------|-----|
| Diodo de supresión de chispa | Yes |
|------------------------------|-----|

| | |
|--|-----|
| Protección contra inversion de polaridad | Yes |
|--|-----|

Eléctrico

| | |
|--------------------------------|--------|
| Tipo de fuente de alimentación | 24 VCC |
|--------------------------------|--------|

| | |
|----------------------|-------|
| Consumo de corriente | 1.6 W |
|----------------------|-------|

| | |
|------------------|------|
| Ciclo de trabajo | 100% |
|------------------|------|

Físico

| | |
|---------------------|-----------------------------|
| Dimensiones físicas | 85 x 85 x 35 mm (H x W x D) |
|---------------------|-----------------------------|

Medioambiental

| | |
|------------------|------------------------------------|
| Clasificación IP | IP54 (magnet) IP42 (connection) |
|------------------|------------------------------------|

Regulatory

| | |
|------------|--------|
| Normativas | EN1155 |
|------------|--------|



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 13 June 2022 - 11:22