

# Product data sheet

Specifications



## Heat detector, Intellia EDI-50

FFS06720250

### Main

Range of product	Esmi addressable components for ALC range
Product or component type	Heat detector

### Complementary

[Ue] rated operational voltage	17...28 V DC polarity insensitive
Current consumption	400 µA at 24 V DC standby 3.5 mA at 24 V DC alarm LED on 1 mA at 24 V DC power-up surge 5 mA at 24 V DC remote LED
Material	Body: PC (polycarbonate) FR Terminal: nickel plated stainless steel
Local signalling	2 LED (red) for alarm
Output type	Remote LED optional
Colour	White
Diameter	100 mm
Height	42 mm
Product weight	105 g

### Environment

Standards	EN 54-5
Product certifications	CPR LPCB
IP degree of protection	IP44
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-40...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5.0 cm
Package 1 width	12.5 cm

---

Package 1 Length	12.5 cm
------------------	---------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

RoHS exemption information	Yes
----------------------------	-----

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

---