Product data sheet

Specifications



Multi-criteria detector, Esmi 2251CTLE-W85, smoke, heat, infrared, CO

FFS06710607

Range of product	Esmi addressable components for SLC range
Product or component type	Multisensor detector
Detection type	Smoke Heat Infrared Carbon monoxide

Complementary

Complementary	
[Ue] rated operational voltage	1532 V DC
Current consumption	200 μA at 24 V DC standby 300 μA at 24 V DC standby LED on 7 mA at 24 V DC alarm LED on 10.8 mA at 24 V DC remote LED
Material	Bayblend FR110
Local signalling	Flashing: LED (green) for power ON LED (red) for alarm
Output type	Remote LED optional
Mounting location	Indoor use only
Alarm threshold	60 °C
Colour	White
Cable cross section	02.5 mm²
Diameter	102 mm
Height	68 mm (with mounting base)
Product weight	130 g

Environment

Standards	Class A1R EN 54-5 EN 54-7
Product certifications	CPD LPCB
Relative humidity	1590 % non-condensing
Ambient air temperature for operation	-2055 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	160.0 g
Package 1 Height	6.0 cm
Package 1 width	11.0 cm
Package 1 Length	11.0 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information