

Product data sheet

Specifications



Detector base beacon sounder, BSS-PR-N33, without isolator

FFS06711724

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Mounting base

Complementary

Product destination	Audible visual alarm
Colour tint	Body: pure white Lens: red
[Ue] rated operational voltage	15...29 V DC
Current consumption	120 µA standby 13.9 mA alarm
Signalling type	32 tones alarm
Acoustic level	91...97 dBA at 1 m
Type of setting	Volume: low settings Volume: medium settings Volume: high settings
Local signalling	LED red flashing at 1 Hz: alarm
Cable cross section	1.5...2.5 mm²
Device mounting	Base mounting low profile Base mounting deep base
Diameter	121 mm
Height	64 mm (low profile) 119 mm (deep base)
Net weight	200 g

Environment

Standards	EN 54-3
Product certifications	LPCB CPR
IP degree of protection	IP21C with low profile base IP44 with deep base
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	232.0 g
Package 1 Height	6.0 cm
Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information