

# Product data sheet

Specifications



## Carbon monoxide detector, Intellia EDI-60

FFS06720260

### Main

Range of product	Esmi addressable components for ALC range
Product or component type	Carbon monoxide detector
Detection type	Carbon monoxide

### Complementary

[Ue] rated operational voltage	17...28 V DC polarity sensitive
Current consumption	500 µA at 24 V DC standby 750 µA at 24 V DC standby peak 3.5 mA at 24 V DC alarm LED on 1 mA at 24 V DC power-up surge 5 mA at 24 V DC remote LED
Material	Body: PC (polycarbonate) FR Terminal: nickel plated stainless steel
Operating altitude	< 2000 m
Local signalling	2 LED (red) for alarm
Output type	Remote LED optional
Colour	White
Diameter	100 mm
Height	42 mm
Product weight	105 g

### Environment

IP degree of protection	IP44
Relative humidity	15...90 % non-condensing
Ambient air temperature for operation	0...50 °C continuous -20...55 °C transient
Ambient air temperature for storage	-10...30 °C continuous -40...55 °C transient

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g

<b>Package 1 Height</b>	5.0 cm
<b>Package 1 width</b>	12.5 cm
<b>Package 1 Length</b>	12.5 cm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>