

Product data sheet

Specifications



Beacon, ESI-80, loop powered

FFS06728080

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Visual alarm device

Complementary

Colour tint	Body: white Lens: red
Device composition	beacon in PC (polycarbonate) contacts in stainless steel
[Ue] rated operational voltage	17...28 V DC polarity insensitive
Current consumption	150 µA at 24 V DC standby 3 mA at 24 V DC alarm 1 mA power-up surge for 100 ms
Local signalling	LED red flashing at 1 Hz: alarm
Diameter	115 mm
Height	38 mm
Net weight	140 g

Environment

IP degree of protection	IP23D
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5.0 cm
Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information