

Product data sheet

Specifications



Heat detector, Esmi Impresia

FFS06741002

Main

Range of product	Esmi addressable components for ELC range
Product or component type	Heat detector

Complementary

[Ue] rated operational voltage	15...32 V DC 27 V DC nominal
Current consumption	290 µA at 27 V DC standby 6.5 mA alarm
Provided equipment	Isolator
Output type	Alarm output 7.5 V 7.5 mA
Cable cross section	0.4...2.0 mm ²
Diameter	103 mm
Height	48.3 mm (with mounting base)
Product weight	81.5 g without mounting base

Environment

Standards	Class A1R EN 54-5 Class A2S EN 54-5 Class BS EN 54-5 EN 54-17
Product certifications	CPR
IP degree of protection	IP30
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.8 cm
Package 1 Width	10.8 cm
Package 1 Length	36.5 cm
Package 1 Weight	88 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)