

# Product data sheet

Specifications

## Base sounder, Esmi Impresia

FFS06741016



### Main

Range of product	Esmi addressable components for ELC range
Product or component type	Mounting base

### Complementary

Product destination	Audible alarm
Colour tint	White
Device composition	body in ABS (acrylonitrile butadiene-styrene)
[Ue] rated operational voltage	16...32 V DC
Current consumption	470 µA at 27 V DC standby 9.8 mA at 27 V DC alarm
Signalling type	32 tones alarm
Acoustic level	79...95 dB at 1 m low volume 95...103 dBA at 1 m high volume
Provided equipment	Isolator
Cable cross section	0.4...2.0 mm <sup>2</sup>
Diameter	102 mm
Height	33 mm
Net weight	127 g

### Environment

Standards	EN 54-3 EN 54-17
Product certifications	CPR
IP degree of protection	IP21C
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm

Package 1 Width	10.6 cm
Package 1 Length	10.6 cm
Package 1 Weight	152 g

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Recommended replacement(s)