

Product data sheet

Specifications



Manual call point, Esmi Impresia, IP67

FFS06741005

Main

Range of product	Esmi addressable components for ELC range
Product or component type	Manual call point
Colour tint	Red

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Control type	Resettable
[Ue] rated operational voltage	15...32 V DC
Current consumption	160 µA at 27 V DC standby 3 mA alarm
Cable cross section	0...2.5 mm² cable
Height	114 mm
Mounting location	Indoor Outdoor
Width	114 mm
Depth	80 mm
Product weight	262 g

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-10...60 °C
Standards	EN 54-11 EN 54-17
Product certifications	CPR
Relative humidity	0...96 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	11.8 cm

Package 1 Length	11.8 cm
Package 1 Weight	325 g
Offer Sustainability	
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)