



Input module, Esmi Impresia, 4 inputs

FFS06741010

Main

Range of product	Esmi addressable components for ELC range
Product or component type	Input module

Complementary

Complementary	
[Ue] rated operational voltage	1532 V DC
Current consumption	300 μA at 27 V DC standby 330 μA at 27 V DC nominal 4 mA LED on 7 mA 2 LEDs on
Colour	Grey
Material	PS (polystyrene)
Provided equipment	Isolator
Cable cross section	0.42.0 mm²
Number of inputs	4 for input circuit
Mounting location	Indoor Outdoor
Length	176 mm
Height	57 mm
Width	126 mm
Net weight	320 g

Environment

Standards	EN 54-17 EN 54-18
Product certifications	CPR
IP degree of protection	IP55
Relative humidity	096 % non-condensing
Ambient air temperature for operation	-1060 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	6 cm
Package 1 Width	12.8 cm
Package 1 Length	18.2 cm
Package 1 Weight	402 g

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)