



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: **IECEX UL 17.0082** Page 1 of 4 [Certificate history:](#)  
Status: **Current** Issue No: 2 [Issue 1 \(2019-08-15\)](#)  
[Issue 0 \(2017-11-03\)](#)  
Date of Issue: 2020-01-31  
Applicant: **Bayco Products, Inc.**  
640 S. Sanden Blvd.  
Wylie, TX 75098  
**United States of America**  
Equipment: **Multifunctional Angle Light, Models Nightstick XPP-5566 and Nightstick XPR-5568**  
Optional accessory:  
Type of Protection: **Intrinsic Safety "ia" and Optical Radiation "op is"**  
Marking: Ex ia op is I Ma  
Ex ia op is IIC T4 Ga  
-20°C ≤ Tamb ≤ + 40°C

Approved for issue on behalf of the IECEx  
Certification Body:

**Katy A. Holdredge**

Position:

**Senior Staff Engineer**

Signature:  
(for printed version)

Date:

2020-01-31

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**UL LLC**  
333 Pfingsten Road  
Northbrook IL 60062-2096  
United States of America





# IECEX Certificate of Conformity

Certificate No.: **IECEX UL 17.0082**

Page 2 of 4

Date of issue: 2020-01-31

Issue No: 2

Manufacturer: **Bayco Products, Inc.**  
640 S. Sanden Blvd.  
Wylie, TX 75098  
**United States of America**

Additional  
manufacturing  
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

## STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

**IEC 60079-0:2011** Explosive atmospheres - Part 0: General requirements  
Edition:6.0

**IEC 60079-11:2011** Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"  
Edition:6.0

**IEC 60079-28:2015** Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation  
Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

## TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[US/UL/ExTR17.0093/00](#)

[US/UL/ExTR17.0093/01](#)

[US/UL/ExTR17.0093/02](#)

Quality Assessment Report:

[GB/ITS/QAR13.0005/06](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX UL 17.0082**

Page 3 of 4

Date of issue: 2020-01-31

Issue No: 2

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The devices are multifunction flashlights that are portable and powered by either a rechargeable battery pack Nightstick 5568-BATT, or with Nightstick 5566-Carrier containing three primary cells Energizer EN91 or E91. The device is provided in either red or green both with a metal belt clip, clear lens, black pushbuttons and articulating head.

**Please see Annex for additional information.**

**SPECIFIC CONDITIONS OF USE: NO**



# IECEX Certificate of Conformity

Certificate No.: **IECEX UL 17.0082**

Page 4 of 4

Date of issue: 2020-01-31

Issue No: 2

**DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

Issue 1: Updated temperature code. Revised design of rechargeable packs for Model 5568.

Issue 2: Manufacturer submitted documentation for an alternate component.

**Annex:**

[Annex to IECEx UL 17.0082 Issue 2.pdf](#)



# IECEx Certificate of Conformity

Certificate No.: IECEx UL 17.0082

Issue No.: 2

Page 1 of 2

## TYPE DESIGNATION

Nomenclature:

XP	P	-556	6	G	X
I	II	III	IV	V	VI

- I - Basic Model
- II - P or R
- III = 556
- IV - 6 (only with suffix P) or 8 (only with suffix R)
- V - G for Green or R for Red color
- VI - blank or X indicating strobe functionality

## PARAMETERS RELATING TO THE SAFETY

1.5V/Cell Alkaline Energizer EN91 or E91, 3.7V/Cell Li-ion, IP 67, Um = 10V

## MARKING

Marking has to be readable and indelible; it has to include the following indications:

**Bayco Products, Inc. XPP-5566**  
**640 S. Sanden Blvd., Wylie, TX 75098**



E 467756  
 ID 4003544

ELECTRICAL SAFETY  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE



Control Drawing: 5568-CERT-DWG1-03

For Battery Charger Connection see Instruction  
 Manual Drawing: 5562-68-MECH-DWG1-09

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

For use with Bayco Li-ion Battery Pack 5568-BATT or  
 5566-CARRIER with 3 AA Energizer Type EN91 or E91  
 batteries only

CLASS I DIV 1 GRPS A-D T4  
 CLASS II & III DIV1 GRPS E-G T135°C  
 CLASS I ZONE 0 AEx ia IIC T4 Ga  
 Ⓢ I M1 Ex ia op is I Ma  
 Ⓢ II 1 G Ex ia op is IIC T4 Ga

Ex ia op is I Ma  
 Ex ia op is IIC T4 Ga  
 DEMKO 17 ATEX 1927  
 IECEx UL 17.0082  
 -20°C ≤ Tamb ≤ +40°C  
 1.5V/Cell Alkaline  
 3.7V/Cell Li-ion  
 IP-67  
 Um: 10V

SEE INSTRUCTION MANUAL  
 VOIR MANUEL

MFG MM-YY



# IECEx Certificate of Conformity

Certificate No.: IECEx UL 17.0082

Issue No.: 2

Page 2 of 2

**Bayco Products, Inc. XPR-5568**  
**640 S. Sanden Blvd., Wylie, TX 75098**



E 467756  
ID 4003544  
ELECTRICAL SAFETY  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE



Control Drawing: 5568-CERT-DWG1-03

For Battery Charger Connection see Instruction  
Manual Drawing: 5562-68-MECH-DWG1-09

 SEE INSTRUCTION MANUAL  
VOIR MANUEL

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
For use with Bayco Li-ion Battery Pack 5568-BATT or  
5566-CARRIER with 3 AA Energizer Type EN91 or E91  
batteries only

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV1 GRPS E-G T135°C  
CLASS I ZONE 0 AEx ia IIC T4 Ga  
Ⓢ I M1 Ex ia op is I Ma  
Ⓢ II 1 G Ex ia op is IIC T4 Ga

Ex ia op is I Ma  
Ex ia op is IIC T4 Ga  
DEMKO 17 ATEX 1927  
IECEx UL 17.0082  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell Alkaline  
3.7V/Cell Li-ion  
IP-67  
Um: 10V

MFG MM-YY