Advantronic

CPR - DECLARATION of PERFORMANCE

N° AT0610CPR (Conformity EU 305/2011)

1. Unique identification code of the product type:

AT410A Advantronic Systems SL AT430A Advantronic Systems SL AT420A Advantronic Systems SL

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4) of the CPR:

AT410A Analogue Addressable Photoelectric Smoke Detector with Short Circuit Isolator AT430A Addressable Multi-criteria Detector with Short Circuit Isolator AT420A Analogue Addressable Class P Heat Detector with Short Circuit Isolator

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use in compatible fire detection and alarm system

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article 11(5):

ADVANTRONIC SYSTEMS, SL
C/Yunque, 9 Nave B1
28760 – Tres Cantos – Madrid - Spain
advantronic@advantronic.es www.advantronic.es

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

AT430A – AT420A: EN 54-5:2000+A1:2002
AT410A – AT430A: EN 54-7:2000+ A1:2002+A2:2006
AT410A – AT430A – AT420A: EN 54-17:2005
AT430A: CEA 4021:2003

Advantronic

Bre Global Ireland, N.B. No. 2831, performed the necessary initial inspection of the manufacturing plant and the factory production control together with ongoing continuous surveillance and issued the certificate confirming constancy of the conformity of the factory production control

AT410A 2831-CPR-F0628 AT430A 2831-CPR-F0629 AT420A 2831-CPR-F0630

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. Declared performance:

ESSENTIAL CHARACTERISTICS	CLAUSE APPLICABLE	PERFORMANCE	HARMONISED STANDARD
Nominal activation conditions / Sensitivity,	4.2, 4.3, 5.2 to 5.6,	PASS	
Response delay (response time) and	5.8, 6.2 (Suffix R)		
Performance under fire conditions			
Operational reliability	4.4 to 4.11	PASS	
Tolerance to supply voltage	5.7	PASS	
Durability of operational reliability and	5.9, 5.10	PASS	
response delay; temperature resistance	5.14 to 5.17	DACC	EN 54 5,2000 ; A1,2002
Durability of operational reliability; vibration resistance	5.14 (0 5.17	PASS	EN 54-5:2000+A1:2002
Durability of operational reliability;	5.11, 5.12	PASS	
humidity resistance	3.11, 3.12	PASS	
Durability of operational reliability;	5.13	PASS	
corrosion resistance			
Durability of operational reliability;	5.18	PASS	
electrical stability			
	T		
Nominal activation conditions / Sensitivity,	4.8, 5.2, 5.3, 5.4,	PASS	
Response delay (response time) and	5.6, 5.7, 5.18		
Performance under fire conditions	121 17 101	DAGG	
Operational reliability	4.2 to 4.7, 4.9 to 4.11	PASS	
Tolerance to supply voltage	5.5	PASS	
Durability of operational reliability and	5.8, 5.9	PASS	
response delay; temperature resistance			EN 54-7:2000+
Durability of operational reliability;	5.13 to 5.16	PASS	A1:2002+A2:2006
vibration resistance			
Durability of operational reliability;	5.10, 5.11	PASS	
humidity resistance			
Durability of operational reliability;	5.12	PASS	
corrosion resistance			
Durability of operational reliability;	5.17	PASS	
electrical stability			

Advantronic

ESSENTIAL CHARACTERISTICS	CLOSE APPLICABLE	PERFORMANCE	HARMONISED STANDARD
Performance parameters under fire conditions	5.2	PASS	
Operational reliability	4	PASS	EN 54-17:2005
Durability of operational reliability, temperature resistance	5.4, 5.5	PASS	
Durability of operational reliability, vibration resistance	5.9 to 5.12	PASS	
Durability of operational reliability, humidity resistance	5.6, 5.7	PASS	
Durability of operational reliability, corrosion resistance	5.8	PASS	
Durability of operational reliability, electrical stability	5.3, 5.13	PASS	

10. The performance of the products identified in points 1 and 2 are in conformity with the declared performance in the point 9. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Andrés Martínez – General Manager – Advantronic Systems SL, Tres Cantos – Madrid - Spain

Tres Cantos, 15 Nov 2019

Andrés Martínez General Manager