

NPD-5004-POE Midspan PoE Injector

www.boschsecurity.com



BOSCH

Invented for life



- Makes PoE cameras easy to install
- Allows one-wire connection
- Reduces power supply requirements
- Compact and cost effective solution
- Supplies up to 15.4 W per port

This power injector allows an existing Ethernet infrastructure to be enhanced for use with PoE cameras.

System overview

The NPD-5004-POE four-port power injector can supply four individual PoE cameras with power.

Functions

The injector converts the AC input power to a +48 VDC power supply which is then provided to the cameras via the Ethernet cable. They support up to 10/100/1000 Mbps pass-through data rates. Each injector provides up to 15.4 W per port. The PoE midspan injector unit can be easily mounted on a shelf, wall or ceiling

Certifications and approvals

Standards	FCC Part 15, Class B
	EN 60950
	EN 55022 class B
	EN 55024
	IEEE 802.3af

Approvals	UL, cUL, FCC, VCCI, GS mark
Regulatory compliance	CE, RoHS, WEEE,

Region	Certification
Europe	CE

Parts included

- PoE midspan injector unit
- Power cord

Technical specifications

Power	
Input supply voltage	100 to 240 VAC; 50/60 Hz
Maximum input current	1 A @ 110 VAC; 0.4 A @ 240 VAC
Output supply voltage	+ 48 VDC nominal
Output port power	15.4 W max.

Input/output

Power input connector	IEC 60320
Ethernet connection	Shielded RJ45 connector; EIA 568A and 568B
Data	10/100/1000 Mbps pass-through data rates

Mechanical

Dimensions (W x H x L)	148 x 43 x 224 mm (5.82 x 1.69 x 8.82 in)
Weight	620 g (1.4 lb)

Environmental

Operating Temperature	0°C to +40°C (32°F to 104°F)
Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Operating Humidity	90% RH max. non-condensing
Storage Humidity	95% RH max. non-condensing
Thermal rating	51 BTU/hour

Ordering information**NPD-5004-POE Midspan PoE Injector**

Power-over-Ethernet midspan injectors for use with PoE enabled cameras; 15.4 W, 4-ports

Order number **NPD-5004-POE**

Represented by:**North America:**

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
203 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

Latin America and Caribbean:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com