

UQGS.S5022 - Heat-automatic Fire Detectors

Heat-automatic Fire Detectors

APOLLO FIRE DETECTORS LTD
 36 BROOKSIDE RD
 HAVANT, P09 1JR United Kingdom

S5022

Model No.	Type	Compatibility Restrictions	Contact Arrangement	Temp Range (°F)	Spacing (Ft)	
					Smooth Ceiling	to Wall or Partition
58000-750, 58000-751USM	FT	D5	NC	135°F	-	-
SA5150-750APO	FT/ROR	D3	-	-	-	-

D3 - For connection to a Listed open area protection smoke or heat detector head with which compatibility was determined by test or a review of circuit parameters. Refer to the manufacturer's installation instructions for a list of compatible models.

D5 - For use only with Listed control units with which compatibility was determined by test.

FT - Fixed temperature

FT/ROR - Fixed temperature/rate of rise combination

Last Updated on 2022-05-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."