

# FF FCP500

## Intelligent Addressable Fire Alarm Panel



1450g/01



0832-CPR-F2828

**EN54-2**  
**EN54-4**

### Features

- Intelligent Addressable Fire Alarm Panel
- 7" Color LCD Display
- 1-4 Loop Options
- 255 Loop address capacity
- Network Car
- 48 LED Display
- 5 Output
- Alarm- Fault Output
- RS232-RS485-CAN-USB Interface Communication
- EN54-2 ve EN54-4 Certified
- 1000 Event Memory
- Optional Internal Printer Connection
- LPCB Approved
- CPR Certificated

### Technical Specifications

Operating voltage	230V AC
Operating Frequency	50 Hz
Operating Current	3A
Battery	2 x 12V DC 12Ah
Operating voltage	24V DC
Loop Voltage	24V DC
Operating temperature	0°C~+40°C
Storage Temperature	0°C~+40°C
Moisture Bond	≤95%
Size (E-Y-D)	420x560x140 mm
LPCB document no.	1450g/01
CPR document no.	0832-CPR-F2828

### Order Details

- FF FCP500-1L Intelligent Addressable Fire Alarm Panel, 1 loop , 1x255 Address Capacity, 48 LED display
- FF FCP500-Loop FCP500 Loop Card 1 loop , 255 Adres Kapasiteli
- FF FCP500-NET FCP500 Network Card
- FF FCP500-PRT FCP500 Internal Printer

Doc: FF FCP500 Datasheet\_GB 01/2020

Fire & Gas Alarm System • CCTV System • PAVA System • Emergency Lighting System • Access Control System • Integration System • Reasure

**Finder Yangın Güvenlik Elektronik Sistemler A.Ş.**

Kepez Mah. 5071 Sok. No:10 07090 Kepez / ANTALYA

T: +90 242 259 04 20

F: +90 242 259 28 88

▶ info@finder.com.tr



▶ www.finder.com.tr